CLAIMS

A compensated pixel driver circuit for an organic electroluminescent device, wherein the circuit comprises a unity gain buffer.

- 2. A compensated pixel driver circuit as claimed in claim 1, wherein the unity gain buffer is implemented as an operational amplifier.
- 3. A compensated pixel driver circuit as claimed in claim 1 or claim 2, wherein the buffer is connected to have unity gain.
- A compensated pixel driver circuit as claimed in claim 2, wherein the circuit comprises a transistor connected so as to act as a current switch for storing voltage on the said capacitor.
- 5. A compensated pixel driver circuit as claimed in any preceding claim, wherein the buffer comprises a differential pair circuit and a driver circuit.
- 6. A compensated pixel driver circuit as claimed in claim 5, wherein the differential pair circuit comprises two transistors whose gates respectively provide an inverting input and a non-inverting input of the buffer and a further transistor whose gate provides a bias voltage input of the buffer.

1

UT TU

- A compensated pixel driver circuit as claimed in claim 5 or claim 6, wherein the driver circuit comprises two transistors connected in series with the output of the buffer being taken from the said connection between these transistors.
- 8. A compensated pixel driver circuit as claimed in any preceding claim, wherein the circuit is implemented with polysilicon thin film transistors.
- 9. A method of compensating the current supply to an organic electroluminescent pixel comprising the step of using an buffer to provide a self adjusting load.
 - 10. An organic electroluminescent display device comprising one or more compensated pixel driver circuits as claimed in any of claims 1 to 8.